

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number  
**WO 2004/041126 A1**

(51) International Patent Classification<sup>7</sup>: **A61F 2/06**

(21) International Application Number:  
PCT/EP2002/012509

(22) International Filing Date:  
8 November 2002 (08.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants and

(72) Inventors: SEGUIN, Jacques [FR/FR]; 27 rue Joubert,  
F-75009 PARIS (FR). LABORDE, Jean-Claude [FR/FR];  
7, rue des Hérons, F-34000 Montpellier (FR).

GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,  
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: ENDOPROSTHESIS FOR VASCULAR BIFURCATION



(57) Abstract: This invention features apparatus and kits for treating an area of vas-  
cular bifurcation where a principal conduit (2) separates into at least two secondary  
conduits (3), the apparatus having at least a first segment that has, in a predetermined  
fully expanded state, a substantially conical shape and a first end (6) having a greater  
diameter than a second end (5); the first end conforming to an increasing cross sec-  
tion of the principal conduit in the direction of at least one secondary conduit, and the  
apparatus being shaped to be independent of any other surgical apparatuses when the  
apparatus is in a predetermined fully expanded state.

WO 2004/041126 A1

## ENDOPROSTHESIS FOR VASCULAR BIFURCATION

## Background of the invention

5       The present invention relates to an apparatus and kit for the treatment of bodily conduits in the area of a bifurcation, that is to say in the area where a principal conduit separates into two secondary conduits. It also relates to equipment for positioning this apparatus.

10       The apparatus and kit of the invention can be used for the treatment of vascular bifurcations, in particular the carotid, femoral, iliac, popliteal, renal or coronary bifurcations, or nonvascular bifurcations, such as tracheal or biliary bifurcations, for example between the common bile and cystic ducts, or in the area of the bifurcation of the principal bile tract.

15       The treatment can consist in re-establishing the appropriate diameter of the bifurcation, in cases of arteriosclerosis or internal cell proliferation, in rectifying a localized or non-localized dissection in the wall of the conduit, or, in cases of aneurysm, in recreating a bifurcation of normal diameter, while eliminating the aneurysmal pouch.

## Description of the prior art

20       It is known to treat narrowing of a rectilinear blood vessel by means of a radially expandable tubular apparatus, commonly referred to as a stent. This apparatus is introduced in the unexpanded state into the internal lumen of the vessel, in particular by the percutaneous route, as far as the area of narrowing. Once in place, it is expanded in such a way as to support the vessel wall and thus re-establish the  
25       appropriate cross section of the vessel.

      The apparatus can be made of a non-elastic material, and in this case is expanded by means of an inflatable balloon on which it is engaged, or can be self-expanding, that is to say made of an elastic material, expanding spontaneously when withdrawn from a sheath which is holding it in the contracted state.

30       United States Patent Nos. 4,733,665 and 4,886,062 are illustrative of existing apparatuses and of corresponding positioning techniques.

      A conventional stent is not entirely suitable for the treatment of a narrowing situated in the area of a bifurcation, since its engagement both in the principal conduit

and in one of the secondary conduits can cause immediate or delayed occlusion of the other secondary conduit.

It is known to reinforce a vascular bifurcation by means of a apparatus comprising two elements, each formed by helical winding of a metal filament. One of the two elements has two parts of diameter corresponding respectively to the diameter of the principal vessel and to the diameter of one of the secondary vessels, and is intended to be engaged on the one hand in this principal vessel and, on the other hand, in this secondary vessel. The other element has a diameter corresponding to the diameter of the other secondary vessel and is coupled to the first element, after the latter has been put into place, by engaging one or more of its turns in the turns of the first element.

This equipment permits reinforcement of the bifurcation but appears unsuitable for treating a vascular narrowing or an occlusive lesion, in view of its structure and of the low possibility of radial expansion of its two constituent elements.

Moreover, the shape of the first element does not correspond to the shape of a bifurcation, which has a widened transitional zone between the end of the principal vessel and the ends of the secondary vessels. Thus, this equipment does not make it possible to fully support this wall or to treat a dissection in the area of this wall. In addition, the separate positioning of these two elements seems relatively difficult.

U.S. Patent No. 5,683,449 to Marcade (Marcade) discloses a bifurcated graft formed from a series of individual components that are intraluminally delivered apart from one another and then assembled to form a fully supported structure. The system includes a base member and one or more grafts connected thereto. Marcade's system requires overlapping connection of its components in order to achieve a fully supported structure and to lock the components to one another, thereby assuring a secure assembly and minimizing the possibility of leakage. Marcade discloses further that systems and methods that do not employ such an overlapping system are prone to acute and chronic failure whereby the graft could become displaced or collapsed.

U.S. Patent No. 6,068,655 to Seguin et al. (the 655 Patent) discloses a apparatus having a first segment that is conical in shape, at least one secondary segment, and a flexible link between segments. The flexible link enables the adjustment of segments relative to each other, but maintains them in connection with one another, limiting their independent positioning.

### Summary of the invention

Prior art apparatuses are not sufficient for treating areas of vascular bifurcation because they require a connection, either direct or indirect, between multiple apparatus segments. This connection forces segments to be aligned relative to one another, as opposed to being aligned according to the shape and curvature of bifurcated vessels to be treated. This decreases the flexibility of the apparatus. In addition, segments connected so as to be directly adjacent or overlapping further decrease the flexibility of the apparatus. Such apparatuses are problematic, for example, for treating a bifurcated secondary conduit that has an axis perpendicular to the axis of the primary conduit.

The present invention aims to overcome various of these disadvantages by making available apparatus with which it is possible to treat a pathological condition in the area of a bifurcation, by fully supporting the vascular wall and by being relatively simple to position.

The apparatus to which the invention relates comprises a conical segment shaped to conform to the shape of the bifurcation in the area of a widened transitional zone. The conical segment is shaped to conform to the increasing cross section of the principal conduit at an area of and facing the vascular bifurcation.

In embodiments, the distal end of the stent may expand to a diameter that is at least about 105% of the diameter of the proximal end of the stent. In embodiments, the distal end of the stent may expand to a diameter that is at least about 110% of the diameter of the proximal end of the stent.

In embodiments, the apparatus comprises only a body (i.e., segment) which has, in a predetermined expanded state, a truncated shape, corresponding to the shape of the bifurcation in the area of the widened transitional zone which separates the principal conduit from the secondary conduits. In this way, only a single stent is required to treat a vascular bifurcation, thereby eliminating the need for the surgical insertion, positioning and coordination of multiple stent segments.

In embodiments, the apparatus comprises:

- at least one radially expandable segment which has, in a predetermined expanded state, a cross section substantially greater than the cross section of one of the secondary conduits; and

- a segment which has, in a predetermined expanded state, a truncated shape, corresponding to the shape of the bifurcation in the area of the widened transitional zone which separates the principal conduit from the secondary conduits.

5 In these embodiments, the segments do not overlap one another, and are not linked together and preferably include no means for being linked together. In this way, optimal positioning of stent segments can be achieved independently from one another. For the purposes of this application, an "unlinked segment" is defined as an independent segment that is neither directly nor indirectly connected to any other surgical apparatus, such as additional stents or segments, when the independent  
10 segment is in its predetermined, fully expanded state.

For the sake of simplification, the segment which has, in the expanded state, a cross section substantially greater than the cross section of one of the secondary conduits will be referred to hereinafter as the "secondary segment," while the segment which has, in the expanded state, a truncated shape will be referred to hereinafter as  
15 the "truncated segment."

In embodiments, the conical stent body may be packaged with a packaging element in a kit for treating an area of vascular bifurcation. In embodiments, the kit may include only the conical stent body and packaging element. Alternatively, the kit may further include at least one secondary stent body.

20 The secondary segment is intended to be introduced into the secondary conduit in the contracted state and to bear, in the expanded state, against the wall of this conduit. This expansion not only makes it possible to treat a narrowing or a dissection situated in the area of this conduit, but also to ensure perfect immobilization of the apparatus in the conduit.

25 In this position of the apparatus, the truncated segment bears against the wall of the conduit delimiting the widened transitional zone of the bifurcation, which it is able to support fully. A narrowing or a dissection occurring at this site can thus be treated by means of this apparatus, with uniform support of the vascular wall, and thus without risk of this wall being damaged.

30 The two non-overlapping, unlinked segments orient themselves suitably independently from each other upon their expansion.

In embodiments, at least the truncated segment is covered by a wall which gives it impermeability in a radial direction.

This wall makes it possible to trap, between it and the wall of the conduit, particles which may originate from the lesion being treated, such as arteriosclerotic particles or cellular agglomerates, and thus to avoid the migration of these particles in the body.

5           Moreover, the apparatus can permit treatment of an aneurysm by guiding the liquid through the bifurcation and thereby preventing stressing of the wall forming the aneurysm.

10           The segments can be made from tubes of material of a different diameter, with the tube for the truncated segment having a larger diameter than the tube for the secondary segment. The tubes may be comprised of the same material. The use of tubes of different diameters results in the truncated segment having a larger radial force, especially at larger diameters.

          Alternatively, the segments can be made from a single tube with different patterns of cuts to result in different shapes and sizes.

15           The apparatus can comprise several secondary segments, placed one after the other, to ensure supplementary support of the wall of the secondary conduit. To this same end, the apparatus can comprise, on that side of the truncated segment directed toward the principal conduit, at least one radially expandable segment having, in the expanded state, a cross section which is substantially greater than the cross section of  
20           the principal conduit.

          According to embodiments of the invention, apparatus segments have a meshwork structure, the meshes being elongated in the longitudinal direction of the apparatus, and each one having a substantially hexagonal shape; the meshes of the truncated segment have a width which increases progressively in the longitudinal  
25           sense of the apparatus, in the direction of the end of this segment having the greatest cross section in the expanded state.

          This increase in the width of the meshes is the result of an increase in the length of the edges of the meshes disposed longitudinally and/or an increase in the angle formed between two facing edges of the same mesh.

30           In addition, the truncated segment can have an axis not coincident with the longitudinal axis of the secondary segment, but oblique in relation to this axis, in order to be adapted optimally to the anatomy of the bifurcation which is to be treated.

          The apparatus can be made of a metal with shape memory. This metal is preferably the nickel/titanium alloy known by the name NITINOL.

The equipment for positioning the apparatus comprises means for permitting the expansion of this apparatus when the latter is in place. These means can comprise a removable sheath in which the apparatus is placed in the contracted state, when this apparatus is made of an elastic material, or a support core comprising an inflatable  
5 balloon on which the apparatus is placed, when this apparatus is made of a non-elastic material.

In either case, this equipment comprises, according to the invention, means with which it is possible to identify, through the body of the patient, the longitudinal location of the truncated segment, so that the latter can be correctly positioned in the  
10 area of the widened zone of the bifurcation.

In the case where the expansion of this same segment is not uniform in relation to the axis of the apparatus, the equipment additionally comprises means with which it is possible to identify, through the body of the patient, the angular orientation of the apparatus in relation to the bifurcation, so that that part of this segment having the  
15 greatest expansion can be placed in a suitable manner in relation to the bifurcation.

#### Brief description of the drawings

To ensure that it is fully understood, the invention is again described hereinbelow with reference to the attached diagrammatic drawings which show, by  
20 way of non-limiting example, embodiments of the apparatuses to which the invention relates.

Figure 1 is a side view thereof, according to a first embodiment;

Figure 2 is a perspective view of apparatuses of the invention in a state of radial contraction, and, in partial cutaway, of the equipment allowing it to be  
25 positioned;

Figure 3 is a longitudinal sectional view of a bifurcation to be treated;

Figures 4 to 6 are views of this bifurcation similar to Figure 3, during three successive stages of positioning of apparatuses of the invention;

Figure 7 is a view, similar to Figure 3, of a bifurcation presenting an aneurysm, in which apparatuses of the invention are placed, and  
30

Figure 8 is a side view of apparatuses according to a second embodiment.

#### Description of embodiments

Figure 1 shows expandable apparatus 1 permitting the treatment of bodily conduits in the area of a bifurcation, that is to say, as is shown in Figure 3, in the area where a principal conduit 2 separates into two secondary conduits 3.

5 In embodiments, the apparatus 1 comprises a conical segment having a proximal end 5 and a distal end 6, and at least one secondary segment(s) having a proximal end 7 and a distal end 8, each of meshwork structure, which are non-overlapping and unlinked as illustrated at 9.

The meshes 10 of these segments are elongated in the longitudinal direction of the apparatus 1 and have in each case a substantially hexagonal shape.

10 The proximal end 5 of the conical segment has a tubular shape and has a diameter which is substantially greater than the diameter of the principal conduit 2.

The distal end 6 of the conical segment has meshes 10 whose width increases progressively, compared to that of the meshes of the proximal end 5, on the one hand in the longitudinal sense of the apparatus 1, in the direction of the end of the distal end 6 situated opposite the proximal end 5.

A transverse increase in the width of the meshes 10 may result from an increase in the length of the edges 10a of the meshes 10 disposed longitudinally, as well as an increase in the angle formed between two facing edges 10a.

20 This conical segment thus has a truncated shape with an axis which is oblique in relation to the longitudinal axis of the apparatus 1. This shape corresponds to the shape of the bifurcation in the area of the widened transitional zone 11 which separates the end of the principal conduit 2 from the ends of the secondary conduits 3.

In various alternate embodiments, the conical segment may continuously taper from the proximal end to the distal end, or the tapering may vary as appropriate.

25 The proximal end 7 and distal end 8 of the secondary segment have an identical diameter, which is substantially greater than the diameter of one of the secondary conduits 3.

30 The apparatus 1 may be made by appropriate cutting of a sheet of nickel/titanium alloy known by the name NITINOL, then folding the resulting blank into a circle and welding the parts of this blank which come into proximity with each other.

This alloy is malleable at a temperature of the order of 10°C but can recover its neutral shape at a temperature substantially corresponding to that of the human body.



Figure 2 shows the apparatus 1 in a state of radial contraction, obtained by cooling its constituent material. During this contraction, the edges 10a pivot in relation to the transverse edges 10b of the meshes 10, in such a way that the meshes 10 have, in this state of contraction, a substantially rectangular shape.

5 By virtue of this contraction, the segments 5 a cross section which is smaller than that of the conduits 2 and 3, and they can be introduced into these, as will be described hereinafter.

10 The apparatus 1 is engaged on a central support core 15, and is then contracted radially on the latter. This core 15 comprises an axial abutment such as a shoulder (not visible in Figure 2) which has a diameter smaller than that of the apparatus 1 when this apparatus is expanded, but greater than the diameter of this apparatus 1 when the latter is contracted. This abutment consequently permits the axial immobilization of the apparatus 1 on the core 15 when the latter is contracted.

15 A sheath 16 is then engaged on the apparatus 1 in order to hold it in its contracted state. This sheath 16 may include, e.g., four radiopaque markers 20, 21, 22, 23 impressed on it, containing, for example, a barium compound. Three markers 20, 21, 22 have an annular 5 shape and extend round the whole periphery of the sheath 16. They are situated, respectively, in the area of the free ends of the segments. The fourth marker 23 is situated at substantially the halfway point of the generatrix of the segment 6. It has a diamond shape and a small thickness.

20 The core 15 has a longitudinal axial hole permitting its engagement on a guide wire 25 (Figures 4 to 6). This wire 25 can be engaged, by the percutaneous route, in the conduit 2, by way of the zone 11, and then in one of the conduits 3, through which it can slide, and comprises a cone 26 of synthetic material, situated in front of the assembly consisting of core 15, apparatus 1 and sheath 16.

25 The bifurcation 30 shown in Figure 3 has excrescences 31 which create a narrowing in cross section, which impedes the flow of the liquid circulating in the conduits 2 and 3. In the case of a vascular bifurcation, these excrescences may be due, for example, to arteriosclerosis or cellular growth.

30 The apparatus 1 permits treatment of this bifurcation by re-establishing the appropriate diameter of the conduits 2, 3 and of the widened zone 11.

As appropriate, depending on whether reinforcement is needed in the secondary conduits, the conical segment may be used alone in the widened area of bifurcation, or it may be used in conjunction with one or more secondary segments.

In practice, as can be seen in Figure 4, the assembly consisting of core 15, apparatus 1 and sheath 16 may be engaged on the wire 25 as far as the cone 26. By means of its sliding action, this wire 25 permits the engagement and then the guiding of this assembly in the conduit 2, the zone 11 and then the conduit 3. The cone 26 facilitates the sliding of the assembly and reduces the risk of trauma.

The marker 22 makes it possible to visualize, with the aid of a suitable radiography apparatus, the position of the conical segment, and thus to visualize the location of the conical segment so that it can be correctly positioned in relation to the widened zone 11.

With the markers 20 and 21 it is possible to ensure that the segments are correctly positioned in the principal conduit 2 and the secondary conduit 3.

The marker 23 is, for its part, visible in a plan view or an edge view, depending on whether it is oriented perpendicular or parallel to the radius of the radiography apparatus. It thus makes it possible to identify the angular orientation of the apparatus 1 in relation to the bifurcation 30, so that the part of the conical segment having the greatest expansion can be placed in an appropriate manner in relation to the zone 11.

The sheath 16, which has a length such that it opens out beyond the opening having permitted introduction of the assembly, is then progressively withdrawn, as is shown in Figures 5 and 6, in order to permit the complete expansion of the apparatus 1. The latter is reheated by the body temperature, and this permits its expansion, or it may expand by simple spring force without temperature effects.. After complete expansion of the apparatus 1, the core 15 and the wire 25 are withdrawn.

Figure 7 shows that the apparatus 1 can also be used to treat an aneurysm 40. At least a portion of the conical segment is covered by a polyester film 41, impermeable to the liquid circulating in the conduits, which film, for example, is sewn onto them. The apparatus then guides this liquid through the bifurcation 30 and consequently prevents stressing of the wall forming the aneurysm 40.

Figure 8 shows a apparatus 100 according to the invention, having segments 105, 106, 107, 108, with a structure similar to that of the segments 5 to 8 in the apparatus shown in Figure 1.

In the apparatus 100, individual segments include six omega-shaped bridges 190. The curved central part 190a of these bridges 190 has a multidirectional elasticity

permitting the appropriate longitudinal orientation of the various segments in relation to one another.

5 The advantage of these bridges 190 is that they provide individual segments, and thus the apparatus, with longitudinal continuity, which facilitates the passage of said apparatus into a highly curved zone and which eliminates the need to reduce this curvature, which is always dangerous in the cases of arteriosclerosis, so as to permit the passage of the apparatus.

10 The invention thus provides apparatuses permitting the treatment of a pathological condition in the area of a bifurcation 30. These apparatuses have the many advantages indicated above, in particular those of ensuring a perfect support of the vessel wall and of being relatively simple to position.

It goes without saying that the invention is not limited to the embodiments described hereinabove by way of example, but instead embraces all the variant embodiments.

15 Thus, the apparatuses 1 and 100 can comprise a single, conical segment, or a conical segment and one or several secondary segments placed one after the other, in order to ensure supplementary support and, if need be, to increase the hold of the apparatus in the bifurcation 30.

20 The core 15 could comprise an inflatable balloon, either to effect the expansion of the apparatus 1, in the case where the latter is made of a nonelastic material, or to ensure the total expansion of a self-expanding apparatus 1 after the latter has been put into place.

The markers 20 to 23 could be impressed on the core 15 or directly on the apparatus 1.

25 The conical segment could have an axis coincident with the longitudinal axis of the apparatus, and not oblique in relation to this axis, if such is rendered necessary by the anatomy of the bifurcation which is to be treated.

30 In addition, the secondary segment could itself have, in the expanded state, a widened shape corresponding to the shape of the widened connecting zone via which, in certain bifurcations, the secondary conduits 3 are connected to the widened transition zone 11. The secondary segment would thus have a shape corresponding to the shape of this widened connecting zone, and would ensure perfect support thereof.

The bridges 190 could be greater or smaller in number than six, and they could have a shape other than an omega shape, permitting their multidirectional elasticity, and in particular a V shape or W shape.

5 As discussed above, the conical stent body may be packaged with a packaging element in a kit for treating an area of vascular bifurcation. In embodiments, the kit may also include only the conical stent body and packaging element. Alternatively, the kit may further include at least one secondary stent body.

10 The stent system described may be adapted as mentioned above to treat any of a number of bifurcations within a human patient. For example, bifurcations of both the left and right coronary arteries, the bifurcation of the circumflex artery, the carotid, femoral, iliac, popliteal, renal or coronary bifurcations. Alternatively this apparatus may be used for nonvascular bifurcations, such as tracheal or biliary bifurcations, for example between the common bile and cystic ducts, or in the area of the bifurcation of the principal bile tract.

## CLAIMS

1. An apparatus for treating an area of bifurcation where a principal body conduit separates into at least two secondary conduits and wherein the principal conduit increases in cross section to the junction with the multiple conduits, said apparatus comprising:

a radially expandable first stent body configured to be engaged in the primary conduit in the area of bifurcation, said first stent body having, in a predetermined fully expanded state, a substantially conical shape and a first end having a greater diameter than a second end, and a cross section substantially greater than a cross section of one of the secondary conduits;

the first stent body being shaped to conform to the increasing cross section of the principal conduit, in the area of a widened transitional zone of the bifurcation that separates the principal conduit from the secondary conduits, in the direction of at least one secondary conduit, said first end opening out in the direction of said secondary conduits upon expansion, and

the first stent body being shaped to be independent of any other stent bodies, and free of any means for connecting to any other stent bodies, when the first stent body is in a predetermined fully expanded state.

2. The apparatus of claim 1, further comprising at least one radially expandable second stent body having, in a predetermined fully expanded state, a substantially cylindrical shape, said second stent body being configured to be engaged in a said secondary conduit;

the cross section of the at least one second stent body, in the predetermined expanded state, being less than the cross section of the first and second ends of the first stent body when the first stent body is in its predetermined expanded state.

3. The apparatus of claim 2, the first stent body being configured to be engaged in the principal conduit only, and the at least one second stent body being configured to be engaged in one secondary conduit only.

4. The apparatus of claim 2, said first and second stent bodies being made from first and second tubes of material, respectively, the second tube having a larger diameter than the first tube.

5. The apparatus of claim 4, said tubes being made of the same material.

6. The apparatus of claim 2, further comprising a plurality of radially expandable second stent bodies capable of being placed one after the other in a said

secondary conduit and having, in the predetermined expanded state, a cross section that is substantially greater than the cross section of that secondary conduit.

7. The apparatus of claim 2, said first and second stent bodies having a meshwork structure formed of meshes elongated in a longitudinal direction of the apparatus, each mesh having a substantially hexagonal shape, wherein the meshes of said second segment have a width which increases progressively in the longitudinal direction of the apparatus with the meshes toward the end of the first stent body having the greatest cross section in the expanded state.

8. The apparatus of claim 2, further comprising at least one radially expandable third segment having, in an expanded state, a substantially cylindrical shape and a cross section that is substantially greater than the cross section of the secondary conduit.

9. The apparatus of claim 1, the diameter of the first stent body continuously decreasing from the first end to the second end thereof.

10. The apparatus of claim 1, the first end being substantially conical and the second end being substantially cylindrical.

11. A kit for treating an area of vascular bifurcation where a principal conduit separates into at least two secondary conduits and wherein the principal conduit increases in cross section to the junction with the multiple conduits, said kit comprising:

a packaging element, and

a radially expandable first stent body configured to be engaged in the primary conduit in the area of bifurcation where a principal conduit separates into at least two secondary conduits and wherein the principal conduit increases in cross section to the junction with the multiple conduits;

the first stent body having, in a predetermined fully expanded state, a substantially conical shape and a first end having a greater diameter than a second end, and a cross section substantially greater than a cross section of one of the secondary conduits,

the first stent body being shaped to conform to the increasing cross section of the principal conduit, in the area of a widened transitional zone of the bifurcation that separates the principal conduit from the secondary conduits, in the direction of at least one secondary conduit, said first end opening out in the direction of said secondary conduits upon expansion, and

the first stent body being shaped to be independent of any other stent bodies, and free of any means for connecting to any other stent bodies, when the first stent body is in a predetermined fully expanded state.

5           12.     The kit of claim 11, said kit consisting only of said packaging element and said first stent body.

          13.     The kit of claim 11, further comprising at least one radially expandable second stent body having, in a predetermined fully expanded state, a substantially cylindrical shape, said second stent body being configured to be engaged in a said secondary conduit;

10           the cross section of the at least one second stent body, in the predetermined expanded state, being less than the cross section of the first and second ends of the first stent body when the first stent body is in its predetermined expanded state.

FIG1











FIG2









## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/12509

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 A61F2/06

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2001/037138 A1 (MAUCH KEVIN A ET AL) 1 November 2001 (2001-11-01) figure 4 paragraphs '0010!', '0011!	1-13
Y	US 6 068 655 A (LABORDE JEAN-CLAUDE ET AL) 30 May 2000 (2000-05-30) cited in the application the whole document	1-13
A	US 2002/035389 A1 (PINCHASIK GREGORY ET AL) 21 March 2002 (2002-03-21) paragraph '0102!	1-13
A	US 5 669 924 A (SHAKNOVICH ALEXANDER) 23 September 1997 (1997-09-23) figure 5	1-13
	----- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*8\* document member of the same patent family

Date of the actual completion of the international search

26 August 2003

Date of mailing of the international search report

30/09/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Franz, V

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 02/12509

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 443 498 A (FONTAINE ARTHUR B) 22 August 1995 (1995-08-22) figure 14 -----	1-13

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 02/12509

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2001037138	A1	01-11-2001	US 6264682 B1	24-07-2001
			US 6165195 A	26-12-2000
			US 2001016767 A1	23-08-2001
			DE 69806550 D1	22-08-2002
			DE 69806550 T2	14-11-2002
			EP 1199052 A2	24-04-2002
			EP 0897700 A1	24-02-1999
			JP 11057019 A	02-03-1999
			US 6221090 B1	24-04-2001
			US 6361544 B1	26-03-2002
			US 6221098 B1	24-04-2001
			US 2001029396 A1	11-10-2001
			US 2001037116 A1	01-11-2001
US 6068655	A	30-05-2000	FR 2749500 A1	12-12-1997
			AU 3180197 A	05-01-1998
			CA 2257340 A1	11-12-1997
			EP 0909147 A1	21-04-1999
			WO 9746174 A1	11-12-1997
			JP 2000511444 T	05-09-2000
US 2002035389	A1	21-03-2002	US 6251133 B1	26-06-2001
			US 6090133 A	18-07-2000
			US 5827320 A	27-10-1998
			US 5755735 A	26-05-1998
			US 5755734 A	26-05-1998
			US 2003074047 A1	17-04-2003
			US 2003125794 A1	03-07-2003
			AU 755759 B2	19-12-2002
			AU 2139999 A	11-11-1999
			AU 3625799 A	23-11-1999
			BR 9901182 A	04-01-2000
			CN 1238221 A	15-12-1999
			DE 19919375 A1	11-11-1999
			EE 9900185 A	15-12-1999
			EE 200200366 A	15-10-2002
			EP 0956832 A1	17-11-1999
			GB 2337002 A ,B	10-11-1999
			WO 9956661 A2	11-11-1999
			JP 11319113 A	24-11-1999
			NO 992163 A	08-11-1999
			NZ 334974 A	23-02-2001
			NZ 506680 A	28-08-2002
			PL 332937 A1	08-11-1999
			SG 76595 A1	21-11-2000
			SK 53899 A3	13-03-2000
			US 2003036793 A1	20-02-2003
			US 6440165 B1	27-08-2002
			US 2001049552 A1	06-12-2001
			US 6117156 A	12-09-2000
			US 2003029039 A1	13-02-2003
			US 6406489 B1	18-06-2002
			AU 729227 B2	25-01-2001
			AU 1998397 A	06-11-1997
			BR 9703057 A	10-11-1998
			CA 2204338 A1	03-11-1997
			CA 2393663 A1	03-11-1997
			CA 2393666 A1	03-11-1997

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 02/12509

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2002035389 A1		CN 1166992 A	10-12-1997
		CZ 9701300 A3	17-12-1997
		DE 19718966 A1	27-11-1997
		EE 9700097 A	15-06-1998
		EE 200100467 A	17-12-2001
		EE 200100468 A	17-12-2001
		EE 200100469 A	17-12-2001
		EP 1040795 A2	04-10-2000
		EP 0804907 A2	05-11-1997
		JP 10043313 A	17-02-1998
		NO 972030 A	04-11-1997
		NO 20012907 A	04-11-1997
US 5669924 A	23-09-1997	AU 7472796 A	15-05-1997
		WO 9715346 A1	01-05-1997
US 5443498 A	22-08-1995	US 5314472 A	24-05-1994
		AU 3539893 A	30-09-1993
		CA 2092337 A1	26-09-1993
		DE 69318614 D1	25-06-1998
		DE 69318614 T2	05-11-1998
		EP 0565251 A1	13-10-1993
		ES 2116406 T3	16-07-1998
		JP 6007454 A	18-01-1994
		US 5527354 A	18-06-1996
		US 5370683 A	06-12-1994